

3660 TS

TWO-SECTION TWIN-LINE® PLANTER



Now available in 12 and 16 row sizes with two-section (TS) manual shut-off of right and left sections. Field tested to be more dependable and equipped with many standard features to fit every operation.

3660 ASD with Interplant, Row Marker and Planter-Mounted PTO Pump options



KINZE COBALT™

Save time and reduce guesswork.

- Manual swath control.
- Variable rate seed control.
- Integrates with radar ground speed sensors.

KINZE ASD

The latest in air seed delivery featuring two centrally-mounted, 55 bushel hoppers (110 total) that distribute seed to individual row units using air pressure. The only moving part is the blower fan! Bottom line, less chance of interruption during the most critical time of year.

THE KINZE FRAME – The backbone of the 3660.

Our three-section frame features added flexibility over traditional Twin-Line® designs – a whopping 6° more up and down. A hydraulic weight transfer mechanism keeps the toolbar even and prevents the wings from rising out of the ground while maintaining consistent seed trench depth. This feature still allows the frame to flex naturally in fields with rolling terrain and terraces. Plus, the 3660 transports as narrow as 11' 2" for better access to and from the field.

LIQUID FERTILIZER OR INTERPLANT®

Can be equipped with Interplant push-row units or a liquid fertilizer package with total capacity of 550 gallons.

KINZE EDGEVAC®

- The leading edge in vacuum seed metering.
- Excellent seed spacing and population control.
- Consistent seed drop from the edge.
- Less tumbling action or ricochet effect inside seed tube.
- Fewer moving parts, less service and maintenance.
- Self-adjusts to maintain the vacuum seal.



KINZE
WWW.KINZE.COM

3660 TS

T W O - S E C T I O N T W I N - L I N E ® P L A N T E R



SPECIFICATION	AIR SEED DELIVERY (ASD)	
Number of Rows	12	16
Weight Empty (Mechanical)	17,040 lb.	19,920 lb.
Weight Empty (EdgeVac)	17,450 lb.	20,400 lb.
Hitch Weight Empty	4,300 lb.	4,300 lb.
Transport Height	11' 11"	11' 11"
Operation Length	23' 1"	26' 1"
Transport Length	39' 10"	49' 10"
Operation Width	35' 2"	45' 2"
Transport Width	11' 2"	11' 2"

KEY FEATURES

- **Kinze Cobalt™** – with PMM electronic seed monitoring.
- **Centrally Located Seed Hoppers** – Equipped with Air Seed Delivery (ASD) uses two centrally-mounted seed hoppers capable of holding a total of 110 bushels.
- **Seed Metering Options** – choose between mechanical or EdgeVac® vacuum seed metering.
- **Frame Flexibility** – 13° up and down movement.
- **Electrically Operated Point-Row Clutches** – provides manual shut-off of right and left sections.
- **Clean Toolbar Design** – vacuum manifolds have been integrated into the toolbar; hydraulic and electrical lines have been encased for protection and organization.
- **Hydraulic Weight Transfer Mechanism** – transfers weight from the center of planter to the wings. This maintains even pressure along the length of the toolbar and prevents the wings from rising out of the ground.
- **Hydraulic Drive** – single motor, variable-rate hydraulic driveline to adjust planting rates from the tractor seat.
- **Optional Breakaway Row Marker Package** – A new design that allows markers to fold back when they hit an obstruction. The marker is returned to service again by simply replacing two shear-bolts.
- **Improved Hitch Clearance** – an additional 8" over other Twin-Line® models.

MORE OPTIONS

- Interplant® Even Row Push Unit
- Rubber V Closing Wheels
- Cast Iron Closing Wheels
- Quick-Adjustable Down Force Springs
- 2-Point Hitch (Cannot be used with planter-mounted PTO driven hydraulic pump.)
- Tractor-Mounted Hydraulic Pump
- Planter-Mounted 2-Section Hydraulic Pump
- Liquid Fertilizer System – two 200 gallon tanks and one 150 gallon tank.
- Liquid Fertilizer Openers
- Liquid Fertilizer Pump
- Granular Chemical Attachments
- Various Row-Unit Attachments



Kinze Manufacturing, Inc.
I-80 at Exit 216 • Williamsburg, Iowa • 52361-0806 USA
www.KINZE.com